

MX-110

Order No. 0203160



1-channel USB recording interface

- Integrated USB audio interface
- Full-duplex USB port (allows for simultaneous recording and reproduction)
- 1 mono input channel with XLR input (mic) and 6.3 mm input (switchable mic/line)
- Selectable 20 dB attenuation and LED level display
- 1 additional stereo input

Model	MX-110
Mic input	2.5 mV, 1 x 3-pole XLR
Line input	45 mV, 1 x 6.3 mm jack 11 k Ω (line)/460 k Ω (inst.)
Aux input	1.25 V, 1 x 3.5 mm jack
Master output	500 mV, 1 x 6.3 mm jack L/R
Aux output	500 mV, 1 x 3.5 mm jack
Headphones	$\geq 16 \Omega$, 1 x 3.5 mm jack
Frequency range	20-20,000 Hz
THD	$\leq 0.03\%$
Crosstalk	92 dB
Power supply	via USB interface $\approx 5\text{ V}/500\text{ mA}$
Operating voltage (possible alternative)	$\approx 5\text{ V}$
Power supply (possible alternative)	500 mA
Dimensions	120 x 50 x 110 mm
Weight	498 g



MX-210

Order No. 0203170



2-channel USB recording interface

- Integrated USB audio interface
- Full-duplex USB port (allows for simultaneous recording and reproduction)
- 2 mono input channels with XLR input (mic) and 6.3 mm input (switchable mic/line)
- Selectable 20 dB attenuation and LED level display
- Input channels switchable mono/stereo
- 1 additional stereo input

Model	MX-210
Mic input	2.5 mV, 2 x 3-pole XLR
Line input	45 mV, 1 x 6.3 mm jack 11 k Ω (line)/460 k Ω (inst.)
Aux input	1.25 V, 1 x 3.5 mm jack
Master output	500 mV, 2 x 6.3 mm jack L/R
Aux output	500 mV, 1 x 3.5 mm jack
Headphones	$\geq 16 \Omega$, 1 x 3.5 mm jack
Frequency range	20-20,000 Hz
THD	$\leq 0.03\%$
Crosstalk	92 dB
Power supply	via USB interface $\approx 5\text{ V}/500\text{ mA}$
Dimensions	160 x 50 x 110 mm
Weight	634 g



MMX-11USB

Order No. 0202840



2-channel miniature audio mixer, with 3 inputs and USB interface.

- Integrated USB audio interface
- Full-duplex USB port (allows for simultaneous recording and reproduction)
- 1 mono input channel with gain control, 2-way equalizer and pan pot, peak LED
- 1 stereo input channel with level control, 2-way equalizer and balance control
- Tape record/play connections

Model	MMX-11USB
Mic input	0.5 mV, 1 x 3-pole XLR
Line input	150 mV (stereo), 1 x RCA L/R 2 mV (mono), 6.3 mm jack
Tape (play)	420 mV, 1 x RCA L/R
Master output	6 V max., 1 x 3.5 mm jack
Booth output	6 V max., 1 x 3.5 mm jack
Tape (rec)	1 x RCA L/R
Frequency range	20-20,000 Hz
THD	$< 0.05\%$
S/N ratio	81 dB, weighted
Equalizer bass	$\pm 15\text{ dB}/80\text{ Hz}$
Equalizer treble	$\pm 15\text{ dB}/12\text{ kHz}$
Power supply	via USB interface or via encl. power supply
Dimensions	102 x 45 x 140 mm
Weight	430 g



MPX-20USB

Order No. 0202860



3-channel stereo DJ mixer, with USB interface. Plug and mix!

- Integrated USB audio interface
- Full-duplex USB port (allows for simultaneous recording and reproduction)
- 1 microphone input channel
- 2 stereo input channels, switchable line/phono and USB/line/phono
- 1 stereo output channel (master)

Model	MPX-20USB
Mic input	1 mV, 1 x 6.3 mm jack
Line input	450 mV, 2 x RCA L/R
Phono input	9 mV, 2 x RCA L/R
Master output	1 V, 1 x RCA L/R
Record output	1 V, 1 x RCA L/R
Headphones	$\geq 8 \Omega$, 1 x 3.5 mm jack, 1 x 6.3 mm jack
Frequency range	20-20,000 Hz
THD	0.1%
S/N ratio	63 dB, unweighted
Power supply	$\approx 5\text{ V}/500\text{ mA}$ via USB interface
Dimensions	150 x 70 x 140 mm
Weight	700 g

